



THE SERIES 8000 SLIDING DOOR SYSTEM









THE SERIES 8000 SLIDING DOOR SYSTEM





Innovative and energy efficient, the 8000 sliding door is ideal for both residential and commercial applications. Held to the highest standards of quality and performance, the 8000 boasts liquid smooth operation, robust build quality, and a look that will evoke admiration and envy . . . especially in our massive 8 panel, 10' tall configurations.

The use of multiple thermal breaks help make this door a juggernaut against the elements. With 3" stainless steel rollers and flush mount or pull handles, operation is a breeze. And with keyed or thumb turn locking options you will always feel secure.

Whether you need a simple sliding patio door or an entire wall that opens on your world, the 8000 is a perfect choice.

FEATURES

- Thermally broken frame Thermal Strut system
- Max panel size @ 50 sq. ft.

FRAME OPTIONS

| Nail on or Equal Leg (Note: 1 15/16" back leg on sill)

CONFIGURATIONS

 \mid XO, OX, OXXO, XXO, OXX, OXXXXO

GLAZING OPTIONS

- | 1" OA insulated glass
- True divided lites 2 1/8"
- Enhanced Noise Reduction

HARDWARE OPTIONS

- | Flush Mount or Standard Handle (keyed lock available)
- 3" Stainless Steel Rollers

FINISH OPTIONS

- | Clear Anodized, Class I (standard)
- | Bronze Anodized, Class I (standard)
- Kynar Paint (Color Matching Available)
- | Split Finishes

RATINGS & CERTIFICATION

- | NFRC Certified Product
- | Commercial Rating

